

Part No.	Description	Price in Rs.
50866361	Thermo Scientific* Savant* 300 ml flask (order F05659000 flask lid with adaptor separately)	9063
50866458	Thermo Scientific* Savant* Flask lid with adaptor	9254
50866459	Thermo Scientific* Savant* Adapter for VirTis 150-2000 ml flasks	5819
50866460	Thermo Scientific* Savant* Flask lid filter	4484
50866461	Thermo Scientific* Savant* Cold trap adaptor	88433
50866357	Thermo Scientific* Savant* SpeedVac adapter	76604
50866466	Thermo Scientific* Savant* Gas ballast oil return kit	33198
50866468	Thermo Scientific* Savant* 2 ml glass vial	12879
50866469	Thermo Scientific* Savant* 10 ml glass vial	6582
50866470	Thermo Scientific* Savant* 5 ml glass vial	11638
50866471	Thermo Scientific* Savant* Stopper, 13 mm, for use with 2 ml glass vials (H01430008)	11448
50866472	Thermo Scientific* Savant* Stopper, 20 mm for acrylic lid	1431
50866473	Thermo Scientific* Savant* Stopper, 20 mm, for 5 and 10 ml glass vials (H01430048 and H01430042)	15836
50866474	Thermo Scientific* Savant* Cap, for 13 mm OD 2 ml glass vials (H01430008)	8395
50866475	Thermo Scientific* Savant* Cap, for 20 mm OD 5 and 10 ml glass vials (H01430048 and H01430042)	9158
50866476	Thermo Scientific* Savant* Crimper, for 13 mm OD caps	25948
50866477	Thermo Scientific* Savant* Crimper, for 20 mm OD caps	27856
50866478	Thermo Scientific* Savant* Replacement O-ring for flask lid with adaptor (F05659000)	2003
50866353	Thermo Scientific* Savant* Drying tray kit (rack + 6 product trays)	POR
9391369CN	Thermo Scientific* Savant* CryoCool heat transfer fluid (1 liter) (hazardous material; requires special air shipping charges)	12974
50866482	Thermo Scientific* Savant* Tray cell (acrylic chamber, rack, 6 product trays, lid)	POR

## Fume Hoods & Enclosures

Part No.	Description	Price in Rs.
<b>BioSafety Cabinets</b>		
FS1025411	Thermo Scientific* MSC Advantage 1.2, 230V, 50Hz, EN Certified, NF listed	POR
FS1025413	Thermo Scientific* MSC Advantage 1.8, 230V, 50Hz, EN Certified, NF listed	POR
FS0109309	Thermo Scientific* Fixed height floor stand 1.2m, 750mm working height	68114
FS0109311	Thermo Scientific* Fixed height floor stand 1.8m, 750mm working height	81763
FS0109312	Thermo Scientific* Manual adjustable stand 1.2m, 750 to 950mm working height in 50 mm increments	95413
FS0109313	Thermo Scientific* Manual adjustable stand 1.8m, 750 to 950mm working height in 50 mm increments	POR
FS0109314	Thermo Scientific* Electric adjustable stand 1.2m with cable remote control, 750 to 950 working height	POR
FS0109325	Thermo Scientific* Electric adjustable stand 1.8m with cable remote control, 750 to 950 working height	POR
50865638	Thermo Scientific* KFR 12 Foot rest bar for retrofit between sides of support frame KFS 112 and KFS 212	29732
50865640	Thermo Scientific* KFR 18 Foot rest bar for retrofit between sides of support frame KFS 118 and KFS 218	29597
50865715	Thermo Scientific* Tap for flammable gas cylinders 3/8" connection	18515
50865664	Thermo Scientific* Non-combustible gas 3/8" Non-combustible gas tap with long neck for installation in side walls	18515
50865711	Thermo Scientific* Vacuum tap 3/8" connection	18515

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
50865712	Thermo Scientific* Water tap H2O 3/8" connection	18515
FS0109979	Thermo Scientific* IV-Bar	32976
50865726	Thermo Scientific* Replacement armrests KAS 30 Set of 2 arm rests, suitable for all models	14325
FS0109978	Thermo Scientific* Solenoid valve for combustable gas tap	46490
FS0048696	Thermo Scientific* Free standing SPOT30 Mobile UV-C irradiator for set up in the work area only. UV-C power supply is required 51900643	79331
FS0109981	Thermo Scientific* Direct Duct Exhaust Transition 1.2	90818
FS0109982	Thermo Scientific* Direct Duct Exhaust Transition 1.8	POR
FS0109987	Thermo Scientific* Additional exhaust HEPA filter for 1.2m cabinet	POR
FS0109989	Thermo Scientific* Additional exhaust charcoal filter for 1.2m cabinet	POR
FS0109984	Thermo Scientific* Thimble Duct Exhaust Transition 1.2	65411
FS0109985	Thermo Scientific* Thimble Duct Exhaust Transition 1.8	71087
FS0109998	Thermo Scientific* Desinfection tent for formaldehyde disinfection	35949
FS0109994	Thermo Scientific* UV Light Option, Field Installed	70006
FS1900912	Thermo Scientific* UV Light Option, Factory Installed	34057
FS0109996	Thermo Scientific* UV-plug for Spot 30 mobile UV irradiator (must be ordered to use the Spot 30)	22975
FS0082970	Thermo Scientific* One-piece Table Top Module KAM 120	58383
FS0085281	Thermo Scientific* One-piece Table Top Module KAM 180	87439
50865731	Thermo Scientific* KAML120 Lowered work surface section 1200mm width. Constructed in 316 stainless steel	66492
50865738	Thermo Scientific* KAML180 Lowered work surface section 1800mm width. Constructed in 316 stainless steel	98116
<b>Laminar Flow</b>		
FBPCR2	Fisher Scientific* PCR Workstation; ISO 5 Class 100 Air; 15w 254nm UV lamp w/15min timer decontamination; fluorescent lamp; stainless-steel cabinet/removable work surface; painted steel cabinet; 115V 50/60Hz; 24.5L x 28.75W x 35.5 in. H	POR
FB59896	Fisherbrand* PCR cabinet 230V 50/60Hz for PCR reactions	POR
FP8250	PCR-UV Chamber With HEPA Filtration	POR
FP8251	PCR-UV Chamber	POR
FS1013519	Thermo Scientific* Heraeus* HPH 9 HERAGUARD 230V/50HZ	POR
FS1013520	Thermo Scientific* Heraeus* HPH 12 HERAGUARD 230V/50HZ	POR
FS1013521	Thermo Scientific* Heraeus* HPH 15 HERAGUARD 230V/50HZ	POR
FS1013522	Thermo Scientific* Heraeus* HPH 18 HERAGUARD 230V/50HZ	POR
FS1013780	Thermo Scientific* Heraeus* HPH 12/95 HERAGUARD 230V/50HZ	POR
FS1013781	Thermo Scientific* Heraeus* HPH 18/95 HERAGUARD 230V/50HZ	POR
FS1900317	Thermo Scientific* Heraeus* Stainless steel work surface for HPH 9 width 900mm, depth 580mm	22965
FS1900318	Thermo Scientific* Heraeus* Stainless steel work surface for HPH 12 and HPH 12/95 width 1200mm, depth 580mm	22965
FS1900319	Thermo Scientific* Heraeus* Stainless steel work surface for HPH 18 and HPH 18/95 width 1800mm, depth 580mm	42918
FS1900320	Thermo Scientific* Heraeus* Stainless steel work surface for HPH 12/95 width 1200mm, depth 780mm	83578
FS1900321	Thermo Scientific* Heraeus* Stainless steel work surface for HPH 18/95 width 1800mm, depth 780mm	POR
FS1900310	Thermo Scientific* Heraeus* Left hand glass with metal sheet and 3 media valve holes for models: HPH 9, 12, 15, 18, HPH 12/95 and HPH 18/95	29240
FS1900311	Thermo Scientific* Heraeus* Right hand glass with metal sheet and 3 media valve holes for models: HPH 9, 12, 15, 18, HPH 12/95 and HPH 18/95	29240
FS1900313	Thermo Scientific* Heraeus* Monitoring contact for external alarm systems	23969

Prices mentioned are for one unit unless pack size is mentioned in the description

Contact: India Toll Free.: 1 800 209 7001 Fax: 022-6680 3001 / 02 e-mail: qfc.customer@thermofisher.com

Part No.	Description	Price in Rs.
FS1900314	Thermo Scientific* Heraeus* UV irradiator with timer function (automatically switches off after 1/2 hour)	62997
FS1900316	Thermo Scientific* Heraeus* UV irradiator with timer function (automatically switches off after 1/2 hour) and monitoring contact for external alarm systems	85962
FS0044284	Thermo Scientific* Heraeus* Floor stand FS 9 for width 1002mm, height 680mm, depth 800mm, working height ~780mm, weight 25kg	66637
FS0044285	Thermo Scientific* Heraeus* Floor stand FS 12, width 1302mm, height 680mm, depth 800mm, working height ~780mm, weight 28kg	66260
FS0044286	Thermo Scientific* Heraeus* Floor stand FS 15, width 1602mm, height 680mm, depth 800mm, working height ~780mm, weight 31kg	81570
FS0044287	Thermo Scientific* Heraeus* Floor stand FS 18, width 1902mm, height 680mm, depth 800mm, working height ~780mm, weight 34kg	81570
FS0050078	Thermo Scientific* Heraeus* Floor stand FS 9/2, width 1002mm, height 820mm, depth 800mm, working height ~900mm, weight 26kg	78684
FS0050079	Thermo Scientific* Heraeus* Floor stand FS 12/2, width 1302mm, height 820mm, depth 800mm, working height ~900mm, weight 29kg	78307
FS0050080	Thermo Scientific* Heraeus* Floor stand FS 15/2, width 1602mm, height 820mm, depth 800mm, working height ~900mm, weight 32kg	91484
FS0050081	Thermo Scientific* Heraeus* Floor stand FS 18/2, width 1902mm, height 820mm, depth 800mm, working height ~900mm, weight 35kg	91484
FS0051764	Thermo Scientific* Heraeus* Floor stand FS 9/3, width 1002mm, height 1000mm, depth 800mm, working height ~1100mm, weight 26kg	81947
FS0051765	Thermo Scientific* Heraeus* Floor stand FS 12/3, width 1302mm, height 1000mm, depth 800mm, working height ~1100mm, weight 29kg	83202
FS0051766	Thermo Scientific* Heraeus* Floor stand FS 15/3, width 1602mm, height 1000mm, depth 800mm, working height ~1100mm, weight 32kg	98763
FS0051767	Thermo Scientific* Heraeus* Floor stand FS 18/3, width 1902mm, height 1000mm, depth 800mm, working height ~1100mm, weight 35kg	97257
FS0046028	Thermo Scientific* Heraeus* Height-Adjustable Floor Stand FSH 9	85084
FS0046029	Thermo Scientific* Heraeus* Height-Adjustable Floor Stand FSH 12	84708
FS0046030	Thermo Scientific* Heraeus* Height-Adjustable Floor Stand FSH 15	98386
FS0046031	Thermo Scientific* Heraeus* Height-Adjustable Floor Stand FSH 18	98386
FS0051989	Thermo Scientific* Heraeus* Castor Set, Set of 4 castors with installation instructions for HPH stand FS type	35891
FS0048665	Thermo Scientific* Heraeus* Mobile floor stand, with castors, FSM 9, width 1002mm, height 680mm, depth 800mm, working height ~780mm, weight 31kg, contact factory for availability	POR
50865714	Thermo Scientific* Heraeus* Mobile floor stand, with castors, FSM 12, width 1302mm, height 680mm, depth 800mm, working height ~780mm, weight 34kg, contact factory for availability	POR
FS0048666	Thermo Scientific* Heraeus* Mobile floor stand, with castors, FSM 15, width 1602mm, height 680mm, depth 800mm, working height ~780mm, weight 37kg, contact factory for availability	POR
FS0048667	Thermo Scientific* Heraeus* Mobile floor stand, with castors, FSM 18, width 1902mm, height 680mm, depth 800mm, working height ~780mm, weight 40kg, contact factory for availability	POR
50865637	Thermo Scientific* Heraeus* KFR 9 Foot rest bar for retrofit between sides of support frame KFS 19 and KFS 209	27608
50865638	Thermo Scientific* Heraeus* KFR 12 Foot rest bar for retrofit between sides of support frame KFS 112 and KFS 212	29732
50865639	Thermo Scientific* Heraeus* KFR 15 Foot rest bar for retrofit between sides of support frame KFS 115 and KFS 215	27608
50865640	Thermo Scientific* Heraeus* KFR 18 Foot rest bar for retrofit between sides of support frame KFS 118 and KFS 218	29597
FS0052460	Thermo Scientific* Heraeus* Screen Wind protection kit, complete with hinges to fit the control unit for HPH 12 sizes	73790
FS0052462	Thermo Scientific* Heraeus* Screen Wind protection kit, complete with hinges to fit the control unit for HPH 18 sizes	78307
FS0052208	Thermo Scientific* Heraeus* Screen Wind protection kit, complete with hinges to fit the control unit for HPH 9 sizes	82323
FS0052461	Thermo Scientific* Heraeus* Screen Wind protection kit, complete with hinges to fit the control unit for HPH 15 sizes	87594
FS0059171	Thermo Scientific* Heraeus* Night Cover for HPH 9	30495
FS0059172	Thermo Scientific* Heraeus* Night Cover for HPH 12	29993
FS0059173	Thermo Scientific* Heraeus* Night Cover for HPH 12/95	30495
FS0058775	Thermo Scientific* Heraeus* Night Cover for HPH 15	29993
FS0055553	Thermo Scientific* Heraeus* Night Cover for HPH 18	30495

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
FS0056406	Thermo Scientific* Heraeus* Night Cover for HPH 18/95	30495
FS0048897	Thermo Scientific* Heraeus* Brochure bag attachable to the clean bench	1380
50865711	Thermo Scientific* Heraeus* Vacuum tap 3/8" connection	18515
50865712	Thermo Scientific* Heraeus* Water tap H2O 3/8" connection	18515
50865664	Thermo Scientific* Heraeus* Non-combustible gas 3/8" Non-combustible gas tap with long neck for installation in side walls	18515
50865715	Thermo Scientific* Heraeus* Tap for flammable gas cylinders 3/8" connection	18515
FS0051846	Thermo Scientific* Heraeus* GF 3 filter 5 replacement GF 3 filters for benches with a working width of up to 1.2m	10918
FS0051847	Thermo Scientific* Heraeus* 5 replacement GF 3 filters for benches with a working width of up to 1.8m	13177
FS0051851	Thermo Scientific* Heraeus* EU 14 filter for HPH 18/95 including fixing material	POR
FS0051852	Thermo Scientific* Heraeus* EU 14 filter for HPH 12/95 including fixing material	89978
FS0049199	Thermo Scientific* Heraeus* Combustible gas adaptor, cartridge CV360	18071
FS0049718	Thermo Scientific* Heraeus* Hose for natural gas (length 1m)	6526
FS0049719	Thermo Scientific* Heraeus* Hose for propane or butane gas (length 1m)	6526

## Furnaces

Part No.	Description	Price in Rs.
<b>Muffle Furnaces</b>		
1055014A	Fisher Scientific* Isotemp* Furnace, Muffle; Basic; 1125 deg. C maximum heat; 3-button control; Top-mounted exhaust port; Welded steel cabinet with baked-on finish; Ventilated base; 208/240V; 50/60Hz; 1200w; 5A; 0.14 cu. ft.; Small Model	POR
1055058N	Fisher Scientific* Isotemp* Furnace, Muffle; Basic; 1125 deg. C maximum heat; 3-button control; Top-mounted exhaust port; Welded steel cabinet with baked-on finish; Ventilated base; 208/240V 50/60Hz; 3000w; 12.5A; 0.58 cu. ft.; Medium model	POR
10550126N	Fisher Scientific* Isotemp* Furnace, Muffle; Basic; 1125 deg. C maximum heat; 3-button control; Top-mounted exhaust port; Welded steel cabinet with baked-on finish; Ventilated base; 208/240V; 50/60Hz; 4600w; 19.2A; 1.26 cu. ft.; Large	POR
1065014A	Fisher Scientific* Isotemp* Furnace, Muffle Programmable; Ambient to 1125 deg. C; 10-year lithium battery for memory backup; 208/240V 50/60Hz, 1700w, 7.1A; 0.14 cu. ft.; Small model	POR
1065058	Fisher Scientific* Isotemp* Muffle Furnace; Programmable; Ambient to 1125 deg. C; 0.58 cu. ft.; 208/240V 50/60Hz, 3000w, 12.5A	POR
10650126N	Fisher Scientific* Isotemp* Furnace, Muffle Programmable; Ambient to 1125 deg. C; 10-year lithium battery for memory backup; 208/240V 50/60Hz, 1700w, 14.2A; 1.26 cu. ft.; Large model	POR
1075014A	Fisher Scientific* Isotemp* Furnace, Muffle Programmable Forced-Draft; Rugged; Meet ASTM D 3174 ash content testing requirements; 208/240V 50/60Hz; 1700w; 7.1A; 0.14 cu. ft.; Small model	POR
1075058	Fisher Scientific* Isotemp* Furnace, Muffle Programmable Forced-Draft; Rugged; Meet ASTM D 3174 ash content testing requirements; 208/240V 50/60Hz; 3000w; 12.5A; 0.58 cu. ft.; Medium model	POR
<b>Combustion Absorbents &amp; Bedding</b>		
A620500	Fisher Scientific* ALUNDUM RR 60 MESH Packaging: Amber Glass; Quantity: 500g	8434
<b>Combustion Boats</b>		
11474210	Fisher Scientific* Boat, Combustion; Fisher; Heavy-gauge nickel; 3 1/2 x 5/8 x 3/8 in.	531
11474211	Fisher Scientific* Boat, Combustion; Fisher; Nickel with 0.02% carbon content; 3 x 3/4 x 1/2 in.; Resistant to 1370 deg. C (2498 deg. F); Flat bottom	482
<b>Muffle Furnaces</b>		
FS0040485	Thermo Scientific* Heraeus* M 104 Muffle Furnace with temperature controller and over-temperature cut-out, 230V	POR
FS0040486	Thermo Scientific* Heraeus* M 104 Muffle Furnace with temperature cut-out and 24-hour timer, 230V	POR
FS0040487	Thermo Scientific* Heraeus* M 104 Muffle Furnace with exhaust flue, 230V	POR
FS0040488	Thermo Scientific* Heraeus* M 104 Muffle Furnace with programmer and over-temperature cut-out, 230V	POR

Prices mentioned are for one unit unless pack size is mentioned in the description