

Part No.	Description	Price in Rs.
FB51664	Fisherbrand* Mixer blender accessory for BagRack 100 for FB51658	20961
FB68460	Fisherbrand* Mixer Whirlmixer Plus vortex base unit only with variable speed control allowing for interchangeable platforms 230V 50/60Hz 75W overall 200-2800rpm, platform 200-1400rpm 150mm x 175mm x 150mm	50914
FB68461	Fisherbrand* Platform for 2 x 25mL flasks	6567
FB68462	Fisherbrand* Platform for microtitre plate	5978
FB68463	Fisherbrand* Platform for 1.5mL microtubes	5251
FB68464	Fisherbrand* Cup for mixing up to 25mm dia. tubes	3953
FB68465	Fisherbrand* Platform for PCR* plate	10198
FB68780	Fisherbrand* Mixer rotary for general use with adjustable angle base unit only 230V 50/60Hz 5 to 30rpm 200mm x 250mm x 175mm	70850
FB68781	Fisherbrand* 24 clip disc for tube diameter 8mm to 11mm	12830
FB68782	Fisherbrand* 12 clip disc for tube diameter 15mm to 17mm	12830
FB68783	Fisherbrand* 6 clip disc for tube diameter 27mm to 30mm	12830
FB68784	Fisherbrand* Carousel for 16mm tubes	18357
FB68785	Fisherbrand* Carousel for 25mm tubes	18357
FB68913	Fisherbrand* Disc assembly 3 tier with 24 clips for FB68780 8mm to 11mm tube diameter	27088
FB68914	Fisherbrand* Disc assembly 3 tier with 12 clips for FB68780 15mm to 17mm tube diameter	27088
FB68915	Fisherbrand* Rotary mixer disc for FB68780	12541
FB68916	Fisherbrand* Clip for FB68915 for 8-11mm diameter tubes	252
FB68917	Fisherbrand* Clip for FB68915 for 15-17mm diameter tubes	497
FB68918	Fisherbrand* Clip for FB68915 for 27-30mm diameter tubes	497

Ovens

Part No.	Description	Price in Rs.
Convection Ovens		
13247725G	Fisher Scientific* Isotemp* OVEN GRAVITY Capacity (Chamber Volume): 2.5 cu. ft.; Model: Small Electrical Requirements: 120V 60Hz, 11A, 1300w;	POR
13247737G	Fisher Scientific* Isotemp* Oven, Premium Lab Gravity Flow; 120V 60Hz, 15A, 1800w; Capacity (Chamber Volume): 3.75 cu. ft.; Model: Medium; 23-1/2 L x 25-3/4 W x 33 in. H	POR
13247750G	Fisher Scientific* Isotemp* OVEN PRE GRAVITY Capacity (Chamber Volume): 5.0 cu. ft.; Model: Large Electrical Requirements: 120V 60Hz, 15A, 1800w;	POR
13247725F	Fisher Scientific* Isotemp* Oven; Premium Lab Forced Air; 120V 60Hz, 15A, 1800w; Capacity (Chamber Volume): 2.5 cu. ft.; Model: Small; 23-1/2 L x 25-3/4 W x 26 in. H	POR
13247737F	Fisher Scientific* Isotemp* Oven; Premium Lab Forced Air; 120V 60Hz, 15A, 1800w; Capacity (Chamber Volume): 3.75 cu. ft.; Model: Medium; 23-1/2 L x 25-3/4 W x 33 in. H	POR
13247750F	Fisher Scientific* Isotemp* Oven; Premium Lab Forced Air; 120V 60Hz, 15A, 1800w; Capacity (Chamber Volume): 5.0 cu. ft.; Model: Large; 23-1/2 L x 25-3/4 W x 39-1/4 in. H	POR
13247825F	Fisher Scientific* Isotemp* OVEN PROG Capacity (Chamber Volume): 2.5 cu. ft.; Model: Small Electrical Requirements: 120V 60Hz, 15A4, 1800w;	POR
13247838F	Fisher Scientific* Isotemp* Oven; Programmable Model: Medium; Capacity Chamber: 3.75 cu. ft.; Range: 50-325 deg. . C; Uniformity (200 deg. . C): +/-2 deg. . C; Inside: 18D x 18W x 20 in. H; Exterior: 23-1/2L x 25-3/4W x 33 in. H; 240V 50/60Hz, 14A, 3300w	POR
13247851F	Fisher Scientific* Isotemp* OVEN PROG Capacity (Chamber Volume): 5.0 cu. ft.; Model: Large Electrical Requirements: 240V 50/60Hz, 14A, 3300w;	POR
13247625G	Fisher Scientific* Isotemp* Oven, General Purpose Capacity 2.5 cu. ft.; Temp. range 50 deg. to 225 deg. C; 1325 BTU/hr. at 200 deg. C; 24 air exchanges/hr.; Exterior 23-1/2L x 25-3/4W x 26 in.H; Chamber 18D x 18W x 13-1/2 in. H; 120V 60Hz, 11A, 1300w	POR
13247637G	Fisher Scientific* Isotemp* OVEN STD Capacity (Chamber Volume): 3.75 cu. ft.; Model: Medium Electrical Requirements: 120V 60Hz, 11A, 1300w;	POR

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
13247650G	Fisher Scientific* Isotemp* Oven, Lab; Standard Large Model; 5 cubic feet capacity; 120V 60Hz, 11A, 1300w; 140 lb. shipping weight; 23-1/2 L x 25-3/4 W x 39-1/4 in. H	POR
SPN95603	Fisherbrand* Thermocouples,Oven/Incubator; For Control Circuit Boards no.95913 and no.101922;Fits Fisher 11-690-525, -526, -537, -538, -550, -551 and 11-690-625, -626, -637, -638, -	6724
LC0001	Fisher Scientific* Qualigens* HPLC COLUMN OVEN	30000
LC0002	Fisher Scientific* Qualigens* HPLC COLUMN OVEN WITH INBUILT TEMP CONTROLLER	30000
FS0042293	Thermo Scientific* Heraeus* T 6 Function Line Oven 230V, 50/60 Hz, work space volume: 57l	POR
FS0042303	Thermo Scientific* Heraeus* T 12 Function Line Oven 230V, 50/60 Hz, work space volume: 110l	POR
FS0042309	Thermo Scientific* Heraeus* T 20 Function Line Oven 230V, 50/60 Hz, work space volume: 199l	POR
FS0045756	Thermo Scientific* Heraeus* T 6 Function Line Oven 230V, 50/60 Hz, work space volume: 57l with weekly, mechanical timer	POR
FS0045761	Thermo Scientific* Heraeus* T 12 Function Line Oven 230V, 50/60 Hz, work space volume: 110l with weekly mechanical timer	POR
FS0045766	Thermo Scientific* Heraeus* T 20 Function Line Oven 230V, 50/60 Hz, work space volume: 199l with weekly mechanical timer	POR
FS0042297	Thermo Scientific* Heraeus* UT 6 Function Line Oven 230V, 50/60 Hz, work space volume: 64 l	POR
FS0042305	Thermo Scientific* Heraeus* UT 12 Function Line Oven 230V, 50/60 Hz, work space volume: 112 l	POR
FS0042311	Thermo Scientific* Heraeus* UT 20 Function Line Oven 230V, 50/60 Hz, work space volume: 210 l	POR
FS0045758	Thermo Scientific* Heraeus* UT 6 Function Line Oven 230V, 50/60 Hz, work space volume: 64 l with weekly mechanical timer	POR
FS0045763	Thermo Scientific* Heraeus* UT 12 Function Line Oven 230V, 50/60 Hz, work space volume: 112 l with weekly mechanical timer	POR
FS0045768	Thermo Scientific* Heraeus* UT 20 Function Line Oven 230V, 50/60 Hz, work space volume: 210 l with weekly mechanical timer	POR
FS0043410	Thermo Scientific* Heraeus* UT 12 Function Line Oven 208V, 50/60 Hz, work space volume: 112 l	POR
FS0043412	Thermo Scientific* Heraeus* UT 20 Function Line Oven 208V, 50/60 Hz, work space volume: 210 l	POR
50869075	Thermo Scientific* Heraeus* UT 12 Function Line Oven 208V, 50/60 Hz, work space volume: 112 l with weekly mechanical timer	POR
50869076	Thermo Scientific* Heraeus* UT 20 Function Line Oven 208V, 50/60 Hz, work space volume: 210 l with weekly mechanical timer	POR
FS0042294	Thermo Scientific* Heraeus* T 6 P Function Line Oven 230V, 50/60 Hz, work space volume: 57l, programmable temperature profiles	POR
FS0042304	Thermo Scientific* Heraeus* T 12 P Function Line Oven 230V, 50/60 Hz, work space volume: 110l, programmable temperature profiles	POR
FS0042310	Thermo Scientific* Heraeus* T 20 P Function Line Oven 230V, 50/60 Hz, work space volume: 199l, programmable temperature profiles	POR
FS0045757	Thermo Scientific* Heraeus* T 6 P Function Line Oven 230V, 50/60 Hz, work space volume: 57l, programmable temperature profiles and additional mechanical weekly programmer	POR
FS0045762	Thermo Scientific* Heraeus* T 12 P Function Line Oven 230V, 50/60 Hz, work space volume: 110l, programmable temperature profiles and additional mechanical weekly programmer	POR
FS0045767	Thermo Scientific* Heraeus* T 20 P Function Line Oven 230V, 50/60 Hz, work space volume: 199l, programmable temperature profiles and additional mechanical weekly programmer	POR
FS0042298	Thermo Scientific* Heraeus* UT 6 P Function Line Oven 230V, 50/60 Hz, work space volume: 64 l, programmable temperature profiles	POR
FS0042306	Thermo Scientific* Heraeus* UT 12 P Function Line Oven 230V, 50/60 Hz, work space volume: 112 l, programmable temperature profiles	POR
FS0042312	Thermo Scientific* Heraeus* UT 20 P Function Line Oven 230V, 50/60 Hz, work space volume: 210 l, programmable temperature profiles	POR
FS0045759	Thermo Scientific* Heraeus* UT 6 P Function Line Oven 230V, 50/60 Hz, work space volume: 64 l, programmable temperature profiles and additional mechanical weekly programmer	POR
FS0045764	Thermo Scientific* Heraeus* UT 12 P Function Line Oven 230V, 50/60 Hz, work space volume: 112 l, programmable temperature profiles and additional mechanical weekly programmer	POR
FS0045769	Thermo Scientific* Heraeus* UT 20 P Function Line Oven 230V, 50/60 Hz, work space volume: 210 l, programmable temperature profiles and additional mechanical weekly programmer	POR
50868930	Thermo Scientific* Heraeus* Kelvilog software for documentation of internal temperature via the RS 232 interface	25350
50869047	Thermo Scientific* Heraeus* Connection kit for PC interface cable, 3 m long, adaptor plug 9 to 25 pin	8283
50869051	Thermo Scientific* Heraeus* Access port, top: ø 23 mm for T models	23216

Prices mentioned are for one unit unless pack size is mentioned in the description

Contact: India Toll Free.: 1 800 209 7001 Fax: 022-6680 3001 / 02 e-mail: qfc.customer@thermofisher.com

Part No.	Description	Price in Rs.
50868942	Thermo Scientific* Heraeus* Access port, right-hand wall: ø 18 mm for T models	24471
50868933	Thermo Scientific* Heraeus* Access port, left-hand wall: ø 18 mm for T models	24471
50869052	Thermo Scientific* Heraeus* Access port, top: ø 58 mm for T models	24346
50868943	Thermo Scientific* Heraeus* Access port, right-hand wall: ø 53 mm for T models	25475
50868934	Thermo Scientific* Heraeus* Access port, left-hand wall: ø 53 mm for T models	25600
50869053	Thermo Scientific* Heraeus* Access port, top: ø 23 mm for UT models	23216
50868944	Thermo Scientific* Heraeus* Access port, right-hand wall: ø 23 mm for UT models	24471
50868935	Thermo Scientific* Heraeus* Access port in the middle of the relevant internal surface: Left-hand wall: ø 23 mm for UT models	24346
50869054	Thermo Scientific* Heraeus* Access port, top: ø 58 mm for UT models	24471
50868945	Thermo Scientific* Heraeus* Access port, right-hand wall: ø 58 mm for UT models	25475
50868936	Thermo Scientific* Heraeus* Access port, left-hand wall: ø 58 mm for UT models	25475
50868952	Thermo Scientific* Heraeus* Support frame 780mm, for T/UT 6, T/UT 6 P and B6/UB6	50950
50868885	Thermo Scientific* Heraeus* Support frame 780mm, for T/UT 12, T/UT 12 P and B12/UB12	57225
50868886	Thermo Scientific* Heraeus* Support frame 780mm, for T/UT 20, T/UT 20 P and B20/UB20	56974
50868953	Thermo Scientific* Heraeus* Support frame 300mm, for T/UT 6, T/UT 6 P and B6/UB6	49193
50868887	Thermo Scientific* Heraeus* Support frame 300mm, for T/UT 12, T/UT 12 P and B12/UB12	52581
50868888	Thermo Scientific* Heraeus* Support frame 300mm, for T/UT 20, T/UT 20 P and B20/UB20	52581
50869032	Thermo Scientific* Heraeus* Stacking kit for T/UT 6 and T/UT 6 P	13302
50869033	Thermo Scientific* Heraeus* Stacking kit for T/UT 12 and T/UT 12 P	15059
50869034	Thermo Scientific* Heraeus* Stacking kit for T/UT 20 and T/UT 20 P	16691
50869035	Thermo Scientific* Heraeus* Chrome wire mesh shelf with 2 supports for T 6/T 6 P	5898
50868993	Thermo Scientific* Heraeus* Chrome wire mesh shelf with 2 supports for T 12/T 12 P	9035
50868991	Thermo Scientific* Heraeus* Chrome wire mesh shelf with 2 supports for T 20/T 20 P	14055
50868979	Thermo Scientific* Heraeus* Chrome wire mesh shelf with 2 supports for UT 12/UT 12 P and UB12	9035
50868980	Thermo Scientific* Heraeus* Chrome wire mesh shelf with 2 supports for UT 20/UT 20 P and UB20	14055
50869044	Thermo Scientific* Heraeus* Stainless steel perforated shelf with 2 supports for T 6/T 6 P	11922
50869038	Thermo Scientific* Heraeus* Stainless steel perforated shelf with 2 supports for T 12/T 12 P	14934
50869045	Thermo Scientific* Heraeus* Stainless steel perforated shelf with 2 supports for T 20/T 20 P	17318
50868969	Thermo Scientific* Heraeus* Stainless steel perforated shelf with 2 supports for UT 6/UT 6 P and UB6	11796
50868967	Thermo Scientific* Heraeus* Stainless steel perforated shelf with 2 supports for UT 12/UT 12 P and UB 12	14934
50869114	Thermo Scientific* Heraeus* T 6030 Oven, 230V, 50/60 Hz, work space volume: 30 l	POR
50869116	Thermo Scientific* Heraeus* T 6060 Oven, 230V, 50/60 Hz, work space volume: 57 l	POR
50869117	Thermo Scientific* Heraeus* T 6120 Oven, 230V, 50/60 Hz, work space volume: 107 l	POR
50869118	Thermo Scientific* Heraeus* T 6200 Oven, 230V, 50/60 Hz, work space volume: 196 l	POR
50869113	Thermo Scientific* Heraeus* T 6420 Oven, 400V, 50/60 Hz, 3 phase, work space volume: 409 l	POR
50869119	Thermo Scientific* Heraeus* T 6760 Oven, 400V, 50/60 Hz, 3 phase, work space volume: 751 l	POR
50869084	Thermo Scientific* Heraeus* UT 6060 Oven, 230V, 50/60 Hz, work space volume: 52 l	POR
50869083	Thermo Scientific* Heraeus* UT 6120 Oven, 230V, 50/60 Hz, work space volume: 94 l	POR
50869115	Thermo Scientific* Heraeus* UT 6200 Oven, 230V, 50/60 Hz, work space volume: 180 l	POR
50869120	Thermo Scientific* Heraeus* UT 6420 Oven, 400V, 50/60 Hz, 3 phase, work space volume: 375 l	POR

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
50869121	Thermo Scientific* Heraeus* UT 6760 Oven, 400V, 50/60 Hz, 3 phase, work space volume: 689 l	POR
50868998	Thermo Scientific* Heraeus* Thermicon P temperature controller for T 6030	67641
50868896	Thermo Scientific* Heraeus* Thermicon P temperature controller for T/UT 6060 - 6200	67390
50868910	Thermo Scientific* Heraeus* Thermicon P temperature controller for T/UT 6420 - 6760	67390
50869058	Thermo Scientific* Heraeus* Thermicon P temperature controller - 20-hour timer - mechanical timer with ON/OFF switch - T 6030, T/UT 6420, 6760	11073
50869059	Thermo Scientific* Heraeus* Thermicon P temperature controller - 20-hour timer - mechanical timer with ON/OFF switch - T/UT 6060 - 6200	9744
50868995	Thermo Scientific* Heraeus* Digicon S with analog interface for T 6030 and ST 6030	68017
50868919	Thermo Scientific* Heraeus* Digicon S with analog interface for T/UT 6060-6200 and ST/SUT 6060-6200	67641
50868997	Thermo Scientific* Heraeus* Digicon S with analog interface for T/UT 6420-6760 and ST/SUT 6420-6760	68017
50868779	Thermo Scientific* Heraeus* Eurotherm 2404/P4 with RS 232 interface (for M models only)	POR
50868928	Thermo Scientific* Heraeus* Eurotherm 2404/P4 with RS 422/485 interface (for M models only)	POR
50869008	Thermo Scientific* Heraeus* Adjustable upper temperature limit controller for T 6030 and T/UT 6420-6760	16816
50868990	Thermo Scientific* Heraeus* Adjustable upper temperature limit controller for T/UT 6060-6200	16816
50869007	Thermo Scientific* Heraeus* Adjustable upper and lower temperature limit controller T 6030 and T/UT 6420-6760	72033
50868920	Thermo Scientific* Heraeus* Adjustable upper and lower temperature limit controller T/UT 6060-6200	71656
50868950	Thermo Scientific* Heraeus* Temperature recorder for all models	POR
50869005	Thermo Scientific* Heraeus* PT 100 connection for external temperature recorder for T 6030, T/UT 6420-6760, ST 6030 and ST/SUT 6420-6760	40660
50869060	Thermo Scientific* Heraeus* PT 100 connection for external temperature recorder for T/UT 6060 - 6200 and ST/UT 6060-6200	40660
50868904	Thermo Scientific* Heraeus* NiCr-Ni connection for external temperature recorder for T 6030 and T/UT 6420-6760	41789
50868989	Thermo Scientific* Heraeus* NiCr-Ni connection for external temperature recorder for T/UT 6060 - 6200	42040
50868911	Thermo Scientific* Heraeus* Digital load temperature monitoring for T 6030, T/UT 6420-6760 and all S/ST models	73539
50869002	Thermo Scientific* Heraeus* Digital load temperature monitoring for T/UT 6060 - 6200	73162
50868905	Thermo Scientific* Heraeus* Daily program timer for T 6030, T/UT 6420-6760, ST 6030, ST/UT 6420-6760 and B/UB 6420-6760	29993
50868892	Thermo Scientific* Heraeus* Daily program timer for T/UT 6060 - 6200 and ST/SUT 6060-6200	30118
50868889	Thermo Scientific* Heraeus* Mechanical weekly program timer for T 6030, T/UT 6420-6760, B 6030 and B/UB 6420-6760	32754
50868895	Thermo Scientific* Heraeus* Mechanical weekly program timer for T/UT 6060 - 6200, B 6060-6200 and 6000 M/P	32879
FS1900161	Thermo Scientific* Heraeus* Digital weekly program timer for T 6030, T/UT 6420-6760, B 6030, B/UB 6420-6760 and 6000 M/P	52079
FS1900162	Thermo Scientific* Heraeus* Digital weekly program timer for T/UT 6060 - 6200 and B 6060-6200	52330
50868897	Thermo Scientific* Heraeus* Fresh air blower for UT 6060 - 6760 and SUT 6060-6760	POR
FS1900100	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for T 6030	86088
FS1900101	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for T 6060	97382
FS1900102	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for T 6120	POR
FS1900103	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for T 6200	POR
FS1900106	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for UT 6060	89351
FS1900107	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for UT 6120	POR
FS1900108	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness with inert gas connection for UT 6200	POR
FS1900261	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for T 6030	83076
FS1900262	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for T 6060	93367
FS1900263	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for T 6120	POR
FS1900264	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for T 6200	POR

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
FS1900265	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for UT 6060	90229
FS1900266	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for UT 6120	POR
FS1900267	Thermo Scientific* Heraeus* Inner casing with conditional gas-tightness including throttle valve for UT 6200	POR
50869023	Thermo Scientific* Heraeus* Door hinged on the left for models 6030-6200 only	42417
50866196	Thermo Scientific* Heraeus* Lockable door for all models	32879
50868900	Thermo Scientific* Heraeus* Door window and internal lighting for T 6060, 1 window	83829
50868901	Thermo Scientific* Heraeus* Door window and internal lighting for T 6120, 1 window	83453
50868903	Thermo Scientific* Heraeus* Door window and internal lighting for T 6200, 2 windows	POR
50868906	Thermo Scientific* Heraeus* Door window and internal lighting for T 6420, 3 windows	POR
50868915	Thermo Scientific* Heraeus* Door window and internal lighting for T 6760, 6 windows	POR
50868937	Thermo Scientific* Heraeus* Door window and internal lighting for UT 6060, 1 window	82198
50868938	Thermo Scientific* Heraeus* Door window and internal lighting for UT 6120, 1 window	82198
50868939	Thermo Scientific* Heraeus* Door window and internal lighting for UT 6200, 2 windows	POR
50868940	Thermo Scientific* Heraeus* Door window and internal lighting for UT 6420, 3 windows	POR
50868941	Thermo Scientific* Heraeus* Door window and internal lighting for UT 6760, 6 windows	POR
50869006	Thermo Scientific* Heraeus* Central monitoring connection for T 6030, T/UT 6420-6760, ST 6030, ST/SUT 6420-6760 and B/UB 6420-6760, also requires PT100 flexible sensor	44801
50868898	Thermo Scientific* Heraeus* Central monitoring connection for T/UT 6060 - 6200, and ST/SUT 6060-6200 also requires PT100 flexible sensor	45303
50868987	Thermo Scientific* Heraeus* RS 232 interface computer interface for the Kelvitron controller	22589
50868994	Thermo Scientific* Heraeus* VITON door gasket for T 6030	23216
50868983	Thermo Scientific* Heraeus* VITON door gasket for T/UT 6060 and FT 6060	29240
50868984	Thermo Scientific* Heraeus* VITON door gasket for T/UT 6120	35640
50868982	Thermo Scientific* Heraeus* VITON door gasket for T/UT 6200	42040
50868986	Thermo Scientific* Heraeus* VITON door gasket for T/UT 6760	77931
50868917	Thermo Scientific* Heraeus* Access port top: \varnothing 23 mm for T/UT 6060-6200, ST/SUT 6060-6200 and B 6060-6200	23216
50868946	Thermo Scientific* Heraeus* Access port, right-hand wall: \varnothing 18 mm	24346
50868922	Thermo Scientific* Heraeus* Access port, left-hand wall: \varnothing 18 mm for T 6030, T/UT 6420-6760, ST 6030, ST/SUT 6420-6760, B 6030 and B/UB 6420-6760	24471
50868918	Thermo Scientific* Heraeus* Access port, top: \varnothing 58 mm for T/UT 6060-6200, ST/SUT 6060-6200 and B 6060-6200	24722
50868947	Thermo Scientific* Heraeus* Access port right-hand wall: \varnothing 53 mm	25350
50868909	Thermo Scientific* Heraeus* Access port, left-hand wall: \varnothing 53 mm for T 6030, T/UT 6420-6760, ST 6030, ST/SUT 6420-6760, B 6030 and B/UB 6420-6760	25475
FS0027659	Thermo Scientific* Heraeus* Power access ports with 10 measuring terminals located at the side	65633
50868893	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 220°C for T 6030, T/UT 6060-6200, ST 6030 and ST/SUT 6060-6200	15687
50868907	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 220°C for T/UT 6420-6760 and ST/SUT 6420-6760	18698
50868894	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 300°C for T 6030, T/UT 6060-6200, ST 6030 and ST/SUT 6060-6200	25475
50868908	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 300°C for T/UT 6420-6760 and ST/SUT 6420-6760	29240
50868971	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6030 or T 6030	5898
50868972	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6060 or T 6060	6526
50868974	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6120 or T 6120	10792

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
50868976	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6200 or T 6200	14934
50868977	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6420 or T 6420	17192
50868978	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6760 or T 6760	25350
50868999	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6060, UT 6060 or FT 6060	6526
50869000	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6120 or UT 6120	10792
50869001	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6200 or UT 6200	14934
50869003	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6420 or UT 6420	17192
50869004	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6760 or UT 6760	25350
50868961	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6030, B 6030, ST 6030	9788
50868962	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6060, B 6060, ST 6060	11796
50868963	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6120, B 6120, ST 6120	14934
50868964	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6200, B 6200, ST 6200	17318
50868965	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6420, B 6420, ST 6420	20706
50868966	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6760, B 6760, ST 6760	30369
50869039	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6060 and UT 6060	11796
50869040	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6120 and UT 6120	14055
50869041	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6200 and UT 6200	16565
50869042	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6420, UT 6420 and UB 6420	20706
50869043	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6760, UT 6760 and UB 6760	29616
50868884	Thermo Scientific* Heraeus* Stacking kit for T/UT 6060, B 6060, BB6060, ST/SUT 6060	6526
50868772	Thermo Scientific* Heraeus* Stacking kit for T/UT 6120-6200, ST/SUT 6210-6200, B 6120-6200 or BBK 6220	7530
50869022	Thermo Scientific* Heraeus* Set of 4 height adjustable feet for B 6030 - 6120, B/UB 6200, T/UT 6030 - 6200 and ST/SUT 6030-6200	3388
50868970	Thermo Scientific* Heraeus* Fresh air particle filter for connection to the fresh air vent (intake), for all models	67641
50868949	Thermo Scientific* Heraeus* Fresh air particle filter for use with the fresh air blower	32001
50869028	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6060, ST/SUT 6060, B 6060 or VT 6060 M/P-BL	50448
50869027	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6120, ST/SUT 6120 or B 6120	59484
50868975	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6200, ST/SUT 6200, B 6200 or VT 6130 M/P-BL	58982
50869029	Thermo Scientific* Heraeus* Support frame 300mm for T/UT 6060, ST/SUT 6060 or B 6060	49193
50869030	Thermo Scientific* Heraeus* Support frame 300mm for T/UT 6120, ST/SUT 6120 or B 6120	53460
50868931	Thermo Scientific* Heraeus* Support frame 300mm for T/UT 6200, ST/SUT 6200 or B 6200	53209
50868992	Thermo Scientific* Heraeus* Exhaust air outlet	30871
FS0047372	Thermo Scientific* Heraeus* Klevilog software for documentation of internal temperature via the RS 232 interface	16691
50869047	Thermo Scientific* Heraeus* Connection kit for PC interface cable, 3 m long, adaptor plug 9 to 25 pin	8283
FS0049367	Thermo Scientific* Heraeus* ET 6080 Oven, 230V, 50/60 Hz, work space volume: 80 l	POR
FS0049368	Thermo Scientific* Heraeus* ET 6130 Oven, 230V, 50/60 Hz, work space volume: 130 l	POR
FS0051010	Thermo Scientific* Heraeus* EUT 6130 Oven, 230V, 50/60 Hz, work space volume: 130 l	POR
50869103	Thermo Scientific* Heraeus* WU 6100 Oven, 400V 3/N, 50/60 Hz, work space volume: 95 l	POR
50869104	Thermo Scientific* Heraeus* WU 6100 Heat Circulating Air Oven 230V/3Ph	POR
FS1900182	Thermo Scientific* Heraeus* NiCr-Cr sensor socket with a separate built-in thermocouple	47311
FS0034607	Thermo Scientific* Heraeus* Access port ø 24 mm, in right-hand wall	23844

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
50868779	Thermo Scientific* Heraeus* Eurotherm 2404/P4 with RS 232 interface (for M models only)	POR
50868928	Thermo Scientific* Heraeus* Eurotherm 2404/P4 with RS 422/485 interface (for M models only)	POR
FS1900187	Thermo Scientific* Heraeus* Hours counter	18573
FS1900188	Thermo Scientific* Heraeus* Central monitoring connection	46809
FS0044445	Thermo Scientific* Heraeus* Calibration certificate for 500°C at center of the work space	38024
FS0034234	Thermo Scientific* Heraeus* Additional stainless steel shelf	9788
FS0034246	Thermo Scientific* Heraeus* Support frame 300 mm in height	59484
50869081	Thermo Scientific* Heraeus* LUT 6050 Drying Oven, 230V, 50/60 Hz, work space volume: 105 l	POR
FS0049644	Thermo Scientific* Heraeus* LUT 6050F Drying Oven, 230V, 50/60 Hz, work space volume: 105 l	POR
FS0054144	Thermo Scientific* Heraeus* LUT 6050 Drying Oven, 230V, 50/60 Hz, work space volume: 105 l. With timer option.	POR
FS0040190	Thermo Scientific* Heraeus* LUT 6050 Drying Oven, with Program Controller, 230V	POR
FS0047470	Thermo Scientific* Heraeus* Chromed wire-mesh shelf including 2 shelf supports	10667
FS0035800	Thermo Scientific* Heraeus* FT 6060 Explosion Proof Oven, 230V, 50Hz, work space volume: 50 l	POR
FS0045803	Thermo Scientific* Heraeus* FT 6060 Explosion Proof Oven, 230V, 50Hz, work space volume: 50 l, with window	POR
FS0041302	Thermo Scientific* Heraeus* Exhaust air monitor	POR
FS0041374	Thermo Scientific* Heraeus* Draught breaker	9663
FS0043015	Thermo Scientific* Heraeus* Ventilator (exhaust side)	POR
FS0028869	Thermo Scientific* Heraeus* Air intake filter	27357
50868983	Thermo Scientific* Heraeus* VITON door gasket for T/UT 6060 and FT 6060	29240
50868999	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6060, UT 6060 or FT 6060	6526
FS0045014	Thermo Scientific* Heraeus* Support frame, 780 mm in height	65382
FS1013347	Thermo Scientific* Heraeus* UT 6060 AR Oven, 230 V, 50/60 Hz, work space volume: 52 l, air circulation	POR
50869049	Thermo Scientific* Heraeus* Special shelf for 12 x 50 ml bottles	14306
50869050	Thermo Scientific* Heraeus* Special shelf for 12 x 100 ml bottles	14306
FS0042396	Thermo Scientific* Heraeus* TK 6060 Testing Cabinet, 230V	POR
FS0047091	Thermo Scientific* Heraeus* TK 6120 Testing Cabinet, 230V	POR
FS0049968	Thermo Scientific* Heraeus* UT 6050 N Testing Oven 230V	POR
FS1015300	Thermo Scientific* Heraeus* ST 6030 Sterilizer 230V, 50/60 Hz, work space volume: 30 l	POR
FS1015301	Thermo Scientific* Heraeus* ST 6060 Sterilizer 230V, 50/60 Hz, work space volume: 57 l	POR
FS1015302	Thermo Scientific* Heraeus* ST 6120 Sterilizer 230V, 50/60 Hz, work space volume: 107 l	POR
FS1015303	Thermo Scientific* Heraeus* ST 6200 Sterilizer 230V, 50/60 Hz, work space volume: 196 l	POR
FS1015304	Thermo Scientific* Heraeus* ST 6420 Sterilizer 400V, 50/60 Hz, 3 phase, work space volume: 409 l	POR
FS1015305	Thermo Scientific* Heraeus* ST 6760 Sterilizer 400V, 50/60 Hz, 3 phase, work space volume: 751 l	POR
FS1015306	Thermo Scientific* Heraeus* SUT 6060 Sterilizer 230V, 50/60 Hz, work space volume: 52 l	POR
FS1015307	Thermo Scientific* Heraeus* SUT 6120 Sterilizer 230V, 50/60 Hz, work space volume: 94 l	POR
FS1015308	Thermo Scientific* Heraeus* SUT 6200 Sterilizer 230V, 50/60 Hz, work space volume: 180 l	POR
FS1015309	Thermo Scientific* Heraeus* SUT 6420 Sterilizer 400V, 50/60 Hz, 3 phase, work space volume: 375 l	POR
FS1015310	Thermo Scientific* Heraeus* SUT 6760 Sterilizer 400V, 50/60 Hz, 3 phase, work space volume: 689 l	POR
50869005	Thermo Scientific* Heraeus* PT 100 connection for external temperature recorder for T 6030, T/UT 6420-6760, ST 6030 and ST/SUT 6420-6760	40660
50869060	Thermo Scientific* Heraeus* PT 100 connection for external temperature recorder for T/UT 6060 - 6200 and ST/UT 6060-6200	40660

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
50868911	Thermo Scientific* Heraeus* Digital load temperature monitoring for T 6030, T/UT 6420-6760 and all S/ST models	73539
50868905	Thermo Scientific* Heraeus* Daily program timer for T 6030, T/UT 6420-6760, ST 6030, ST/UT 6420-6760 and B/UB 6420-6760	29993
50868892	Thermo Scientific* Heraeus* Daily program timer for T/UT 6060 - 6200 and ST/SUT 6060-6200	30118
50869006	Thermo Scientific* Heraeus* Central monitoring connection for T 6030, T/UT 6420-6760, ST 6030, ST/SUT 6420-6760 and B/UB 6420-6760, also requires PT100 flexible sensor	44801
50868898	Thermo Scientific* Heraeus* Central monitoring connection for T/UT 6060 - 6200, and ST/SUT 6060-6200 also requires PT100 flexible sensor	45303
50868897	Thermo Scientific* Heraeus* Fresh air blower for UT 6060 - 6760 and SUT 6060-6760	POR
50869023	Thermo Scientific* Heraeus* Door hinged on the left for models 6030-6200 only	42417
50866196	Thermo Scientific* Heraeus* Lockable door for all models	32879
50868917	Thermo Scientific* Heraeus* Access port top: ø 23 mm for T/UT 6060-6200, ST/SUT 6060-6200 and B 6060-6200	23216
50868946	Thermo Scientific* Heraeus* Access port, right-hand wall: ø 18 mm	24346
50868922	Thermo Scientific* Heraeus* Access port, left-hand wall: ø 18 mm for T 6030, T/UT 6420-6760, ST 6030, ST/SUT 6420-6760, B 6030 and B/UB 6420-6760	24471
50868918	Thermo Scientific* Heraeus* Access port, top: ø 58 mm for T/UT 6060-6200, ST/SUT 6060-6200 and B 6060-6200	24722
50868947	Thermo Scientific* Heraeus* Access port right-hand wall: ø 53 mm	25350
50868909	Thermo Scientific* Heraeus* Access port, left-hand wall: ø 53 mm for T 6030, T/UT 6420-6760, ST 6030, ST/SUT 6420-6760, B 6030 and B/UB 6420-6760	25475
50868950	Thermo Scientific* Heraeus* Temperature recorder for all models	POR
50868995	Thermo Scientific* Heraeus* Digicon S with analog interface for T 6030 and ST 6030	68017
50868919	Thermo Scientific* Heraeus* Digicon S with analog interface for T/UT 6060-6200 and ST/SUT 6060-6200	67641
50868997	Thermo Scientific* Heraeus* Digicon S with analog interface for T/UT 6420-6760 and ST/SUT 6420-6760	68017
50869028	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6060, ST/SUT 6060, B 6060 or VT 6060 M/P-BL	50448
50869027	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6120, ST/SUT 6120 or B 6120	59484
50868975	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6200, ST/SUT 6200, B 6200 or VT 6130 M/P-BL	58982
50869029	Thermo Scientific* Heraeus* Support frame 300mm for T/UT 6060, ST/SUT 6060 or B 6060	49193
50869030	Thermo Scientific* Heraeus* Support frame 300mm for T/UT 6120, ST/SUT 6120 or B 6120	53460
50868931	Thermo Scientific* Heraeus* Support frame 300mm for T/UT 6200, ST/SUT 6200 or B 6200	53209
50868884	Thermo Scientific* Heraeus* Stacking kit for T/UT 6060, B 6060, BB6060, ST/SUT 6060	6526
50868772	Thermo Scientific* Heraeus* Stacking kit for T/UT 6120-6200, ST/SUT 6210-6200, B 6120-6200 or BK 6220	7530
50869022	Thermo Scientific* Heraeus* Set of 4 height adjustable feet for B 6030 - 6120, B/UB 6200, T/UT 6030 - 6200 and ST/SUT 6030-6200	3388
50868893	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 220°C for T 6030, T/UT 6060-6200, ST 6030 and ST/SUT 6060-6200	15687
50868907	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 220°C for T/UT 6420-6760 and ST/SUT 6420-6760	18698
50868894	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 300°C for T 6030, T/UT 6060-6200, ST 6030 and ST/SUT 6060-6200	25475
50868908	Thermo Scientific* Heraeus* PT100 flexible temperature sensor, max temperature 300°C for T/UT 6420-6760 and ST/SUT 6420-6760	29240
50868970	Thermo Scientific* Heraeus* Fresh air particle filter for connection to the fresh air vent (intake), for all models	67641
50868949	Thermo Scientific* Heraeus* Fresh air particle filter for use with the fresh air blower	32001
FS0047372	Thermo Scientific* Heraeus* Klevilog software for documentation of internal temperature via the RS 232 interface	16691
50869047	Thermo Scientific* Heraeus* Connection kit for PC interface cable, 3 m long, adaptor plug 9 to 25 pin	8283
50868971	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6030 or T 6030	5898
50868972	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6060 or T 6060	6526

Prices mentioned are for one unit unless pack size is mentioned in the description

Contact: India Toll Free.: 1 800 209 7001 Fax: 022-6680 3001 / 02 e-mail: qfc.customer@thermofisher.com

Part No.	Description	Price in Rs.
50868974	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6120 or T 6120	10792
50868976	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6200 or T 6200	14934
50868977	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6420 or T 6420	17192
50868978	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for ST 6760 or T 6760	25350
50868961	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6030, B 6030, ST 6030	9788
50868962	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6060, B 6060, ST 6060	11796
50868963	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6120, B 6120, ST 6120	14934
50868964	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6200, B 6200, ST 6200	17318
50868965	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6420, B 6420, ST 6420	20706
50868966	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for T 6760, B 6760, ST 6760	30369
50868999	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6060, UT 6060 or FT 6060	6526
50869000	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6120 or UT 6120	10792
50869001	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6200 or UT 6200	14934
50869003	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6420 or UT 6420	17192
50869004	Thermo Scientific* Heraeus* Chrome wire-mesh shelf with 2 shelf supports: for SUT 6760 or UT 6760	25350
50869039	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6060 and UT 6060	11796
50869040	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6120 and UT 6120	14055
50869041	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6200 and UT 6200	16565
50869042	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6420, UT 6420 and UB 6420	20706
50869043	Thermo Scientific* Heraeus* Additional stainless steel perforated shelf including 2 shelf supports: for SUT 6760, UT 6760 and UB 6760	29616
50868895	Thermo Scientific* Heraeus* Mechanical weekly program timer for T/UT 6060 - 6200, B 6060-6200 and 6000 M/P	32879
FS1900161	Thermo Scientific* Heraeus* Digital weekly program timer for T 6030, T/UT 6420-6760, B 6030, B/UB 6420-6760 and 6000 M/P	52079
50868951	Thermo Scientific* Heraeus* Thermicon P temperature programmer (for M models only)	67390
50868779	Thermo Scientific* Heraeus* Eurotherm 2404/P4 with RS 232 interface (for M models only)	POR
50868928	Thermo Scientific* Heraeus* Eurotherm 2404/P4 with RS 422/485 interface (for M models only)	POR
FS0047372	Thermo Scientific* Heraeus* Klevilog software for documentation of internal temperature via the RS 232 interface	16691
50869047	Thermo Scientific* Heraeus* Connection kit for PC interface cable, 3 m long, adaptor plug 9 to 25 pin	8283
50869028	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6060, ST/SUT 6060, B 6060 or VT 6060 M/P-BL	50448
50868975	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6200, ST/SUT 6200, B 6200 or VT 6130 M/P-BL	58982
Vacuum Ovens		
13262280A	Fisher Scientific* Isotemp* Oven, Economy Vacuum 0.67 cu. ft.; 120V 50/60Hz, 1000w, 8.4A; Vacuum: 0 to 30 in.Hg; With 2 adjustable shelves	POR
13262285A	Fisher Scientific* Isotemp* Oven, Economy Vacuum 1.6 cu. ft.; 120V 50/60Hz, 1700w, 14.2A (Comes with domestic 20A plug; 20A service required); Vacuum: 0 to 30 in.Hg; With two adjustable shelves	POR
1326250	Fisher Scientific* HiTemp* VAC OVEN MODEL 281 Electrical Requirements: 120V 50/60Hz	POR
1326252	Fisher Scientific* Isotemp* Oven, Vacuum; Capacity: 1.5 cu.ft.; Full-view chamber door; Self-diagnostics; 7-day programmable timer; Auto time/temp controls; 2 shelves; 115V 50/60Hz	POR
SPN95635	Fisher Scientific* Isotemp* Support;Shelf;Oven;	1607
FS1014539	Thermo Scientific* Heraeus* VT 6060 M Vacuum Oven with jacket heating, 200°C, 230V	POR
50869085	Thermo Scientific* Heraeus* VT 6130 M Vacuum Oven with jacket heating, 200°C, 230V	POR

Prices mentioned are for one unit unless pack size is mentioned in the description

Part No.	Description	Price in Rs.
50869086	Thermo Scientific* Heraeus* VT 6060 P Vacuum Oven with directly heated shelves, 300°C, 230V	POR
50869087	Thermo Scientific* Heraeus* VT 6130 P Vacuum Oven with directly heated shelves, 300°C, 230V	POR
50868987	Thermo Scientific* Heraeus* RS 232 interface computer interface for the Kelvitron controller	22589
50869063	Thermo Scientific* Heraeus* Digital pressure display 2 adjustable switching points and chart recorder output	POR
50868929	Thermo Scientific* Heraeus* Pressure regulation with solenoid valves, 2 switching points and digital display	POR
50868956	Thermo Scientific* Heraeus* Viton door gasket for VT 6060 M/P-BL	67390
50868957	Thermo Scientific* Heraeus* Viton door gasket for VT 6130 M/P -BL	73790
50868916	Thermo Scientific* Heraeus* Daily program timer, mechanical	31499
50869064	Thermo Scientific* Heraeus* 24 hour timer (20 h at 60 hz)	12173
50868955	Thermo Scientific* Heraeus* Digital load temperature display for external data recorder	POR
50868921	Thermo Scientific* Heraeus* Digicon S temperature controller with analog interface 0-20 mA/0-10 V, 200°C: VT 6060 M and VT 6130 M	40911
50868899	Thermo Scientific* Heraeus* Digicon S temperature controller with analog interface 0-20 mA/0-10 V, 300°C: VT 6060 P and VT 6130 P	40911
FS1900196	Thermo Scientific* Heraeus* Digicon S temperature controller with analog interface 0-20 mA/0-10 V, 400°C: VT 6060 P	POR
FS1900197	Thermo Scientific* Heraeus* Digicon S temperature controller with analog interface 0-20 mA/0-10 V, 400°C: VT 6130 P	POR
50866038	Thermo Scientific* Heraeus* Rated temperature 400°C (door without inspection window) for VT 6060 P	81570
50866039	Thermo Scientific* Heraeus* Rated temperature 400°C (door without inspection window) for VT 6130 P	99516
50866198	Thermo Scientific* Heraeus* Central monitoring connection	47060
FS1900075	Thermo Scientific* Heraeus* Vacuum chamber with rounded corners at the rear for VT 6060 M	POR
FS1900077	Thermo Scientific* Heraeus* Vacuum chamber with rounded corners at the rear for VT 6060 P	POR
FS1900076	Thermo Scientific* Heraeus* Vacuum chamber with rounded corners at the rear for VT 6130 M	POR
FS1900078	Thermo Scientific* Heraeus* Vacuum chamber with rounded corners at the rear for VT 6130 P	POR
FS1900368	Thermo Scientific* Heraeus* Chamber PTFE-Coated VT 6060 M	POR
FS1900369	Thermo Scientific* Heraeus* Chamber PTFE-Coated VT 6130 M	POR
50869036	Thermo Scientific* Heraeus* Additional shelf including 2 supports for VT 6060 M-BL	19577
50869037	Thermo Scientific* Heraeus* Additional shelf including 2 supports for VT 6130 M-BL	22589
50868913	Thermo Scientific* Heraeus* Stainless steel tray for VT 6060 M-BL	10918
50868973	Thermo Scientific* Heraeus* Aluminum tray for VT 6060 M-BL	9914
50868914	Thermo Scientific* Heraeus* Stainless steel tray for VT 6130 M-BL	15059
50868988	Thermo Scientific* Heraeus* Aluminum tray for VT 6130 M-BL	14306
50868902	Thermo Scientific* Heraeus* Vacuum connection kit for tubing with a diameter of 10 mm, stainless steel	13302
FS1014546	Thermo Scientific* Heraeus* VT 6060 M-BL Vacuum Oven with jacket heating, max. 200°C, 53 l, 230V	POR
FS1014547	Thermo Scientific* Heraeus* VT 6130 M-BL Vacuum Oven with jacket heating, max. 200°C, 128 l, 230V	POR
FS1014548	Thermo Scientific* Heraeus* VT 6060 P-BL Vacuum Oven with directly heated shelves, max. 300°C, 53 l, 230V	POR
FS1014549	Thermo Scientific* Heraeus* VT 6130 P-BL Vacuum Oven with directly heated shelves, max. 300°C, 128 l, 230V	POR
50868987	Thermo Scientific* Heraeus* RS 232 interface computer interface for the Kelvitron controller	22589
50868956	Thermo Scientific* Heraeus* Viton door gasket for VT 6060 M/P-BL	67390
50868957	Thermo Scientific* Heraeus* Viton door gasket for VT 6130 M/P -BL	73790
FS0042626	Thermo Scientific* Heraeus* Flame filter for solvents	POR

Prices mentioned are for one unit unless pack size is mentioned in the description

Contact: India Toll Free.: 1 800 209 7001 Fax: 022-6680 3001 / 02 e-mail: qfc.customer@thermofisher.com

Part No.	Description	Price in Rs.
50869028	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6060, ST/SUT 6060, B 6060 or VT 6060 M/P-BL	50448
50868975	Thermo Scientific* Heraeus* Support frame 780mm for T/UT 6200, ST/SUT 6200, B 6200 or VT 6130 M/P-BL	58982
50869036	Thermo Scientific* Heraeus* Additional shelf including 2 supports for VT 6060 M-BL	19577
50869037	Thermo Scientific* Heraeus* Additional shelf including 2 supports for VT 6130 M-BL	22589
50868913	Thermo Scientific* Heraeus* Stainless steel tray for VT 6060 M-BL	10918
50868973	Thermo Scientific* Heraeus* Aluminum tray for VT 6060 M-BL	9914
50868914	Thermo Scientific* Heraeus* Stainless steel tray for VT 6130 M-BL	15059
50868988	Thermo Scientific* Heraeus* Aluminum tray for VT 6130 M-BL	14306
50868902	Thermo Scientific* Heraeus* Vacuum connection kit for tubing with a diameter of 10 mm, stainless steel	13302
FS1014550	Thermo Scientific* Heraeus* VT 6025 Vacuum Oven, standard model, 230V, 50/60 Hz	POR
FS1014552	Thermo Scientific* Heraeus* VT 6025 Vacuum Oven, with inert gas connection, 230V, 50/60 Hz	POR
FS1014553	Thermo Scientific* Heraeus* VT 6025 Vacuum Oven, with inert gas connection and digital pressure display with recorder output, 230V, 50/60 Hz	POR
FS1014554	Thermo Scientific* Heraeus* VT 6025 Vacuum Oven, with inert gas connection, digital pressure display with recorder output and Digicon S temperature controller, 230V 50/60 Hz	POR
50868996	Thermo Scientific* Heraeus* Precision control valve only for cat no 51014550	13679
50869026	Thermo Scientific* Heraeus* Additional shelf with 2 shelf supports	15059
50868987	Thermo Scientific* Heraeus* RS 232 interface computer interface for the Kelvicon controller	22589
50868902	Thermo Scientific* Heraeus* Vacuum connection kit for tubing with a diameter of 10 mm, stainless steel	13302
FS0047372	Thermo Scientific* Heraeus* Klevilog software for documentation of internal temperature via the RS 232 interface	16691
50869047	Thermo Scientific* Heraeus* Connection kit for PC interface cable, 3 m long, adaptor plug 9 to 25 pin	8283
FS0040078	Thermo Scientific* Heraeus* Triple stage diaphragm pump.MD12H	POR
FS0028362	Thermo Scientific* Heraeus* Double stage diaphragm pump, chemistry version. HMD4C	POR
FS0028364	Thermo Scientific* Heraeus* Double stage vacuum pump, chemistry version. HMZ2C	POR
FS0028361	Thermo Scientific* Heraeus* Single stage vacuum pump. RE9H, 8,6M3/H	POR
FS0044332	Thermo Scientific* Heraeus* Vacucenter with HMD 8 triple stage diaphragm pump. Suction capacity 6.5 m ³ /hr.	POR
FS0044333	Thermo Scientific* Heraeus* Vacucenter with HMD 4C double stage diaphragm pump, suction capacity 3.0 m ³ /hr	POR
FS0044334	Thermo Scientific* Heraeus* Vacucenter with HRE 8 single stage rotary vacuum pump, suction capacity 8.6 m ³ /hr	POR

Oxygen Analysis

Part No.	Description	Price in Rs.
Benchtop Dissolved Oxygen Meters		
13636AB40	Fisher Scientific* accumet* Kit, Meter Basic AB40; Dissolved oxygen; Benchtop; DO/BOD measurement; 4.25L x 3 in.W (10.8 x 7.6cm) display with 0.75 in. (2cm) high digits; 1 lb. (0.82kg); 115V 60Hz; 7.5L x 5.5W x 3.25 in.H (19 x 14 x 8.3cm)	POR
13636XL40	Fisher Scientific* accumet* Kit, Temperature meter; Fisher Scientific accumet; Dissolved Oxygen/BOD/OUR/SOUR; XL40 meter kit/DO; Custom LCD; Benchtop; Temperature rage: -10.0-+110.0deg.C; 110/220V	POR
3636XL40A	Fisher Scientific* accumet* Meter, Temperature; Fisher Scientific accumet; Dissolved Oxygen/BOD/OUR/SOUR; XL40A DO/Temperature meter only; Benchtop; Custom LCD; Temperature rage: -10.0-+110.0deg.C; 110/220V	POR
Dissolved Oxygen Probe Accessories		
13637DOM	Fisher Scientific* Membrane Kit for DO Probes	11842

Prices mentioned are for one unit unless pack size is mentioned in the description