

Refractometers

Part No.	Description	Price in Rs.
Benchtop Refractometers & Polarimeters		
1396411	Fisher Scientific* Abbe Benchtop Refractometers Electrical Requirements: 220V 50Hz (International Model)	POR
SPN11234	Fisherbrand* Clamps, for Head Assembly in Fisherbrand Refractometer (13-947)	5266
SPN11402	Fisherbrand* Prism, for Fisherbrand 13-947-1 Refractometer	12206

Refrigeration

Part No.	Description	Price in Rs.
Freezers		
979261	Fisher Scientific* Freezer; Undercounter General purpose storage; 5.6 cu. ft.; -20 to -15 deg. C; Manual defrost; 3 fixed shelves; 120V 60Hz	77895
1399088	Fisher Scientific* Isotemp* Freezer, Upright -86 deg. to -50 deg. C; 17.2 cu.ft.; 208/230V 60Hz	POR
1399090	Fisher Scientific* Isotemp* Freezer, Upright -86 deg. to -50 deg. C; 20.2 cu.ft.; 208/230V 60Hz	POR
1399092	Fisher Scientific* Isotemp* Freezer, Upright -86 deg. to -50 deg. C; 24.4 cu.ft.; 208/230V 60Hz	POR
1399006	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright; Capacity: 17.2 cu. ft.; 208/230V 60Hz	POR
1399011	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright; Capacity: 20.2 cu. ft.; 208-230V 60Hz	POR
1399012	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright; Capacity: 20.2 cu. ft.; 230V 50Hz	POR
1399013	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright; Capacity: 20.2 cu. ft.; 230V 50Hz	POR
1399015	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright; Capacity: 24.4 cu. ft.; 208-230V 60Hz	POR
1399016	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright; Capacity: 24.4 cu. ft.; 230V 50Hz	POR
1399029	Fisher Scientific* Isotemp* Freezers Basic Chest; -86 deg. to -40 deg. C; 10.0 cu. ft.; Meet UL and CUL criteria; 208/240V 60Hz	POR
1399033	Fisher Scientific* Isotemp* Freezers Basic Chest; -86 deg. to -40 deg. C; 14.0 cu. ft.; Meet UL and CUL criteria; 208/240V 60Hz	POR
1399034	Fisher Scientific* Isotemp* Freezers Basic Chest; -86 deg. to -40 deg. C; 14.0 cu. ft.; Meet UL and CUL criteria; 220V 50Hz	POR
1399019	Fisher Scientific* Isotemp* Freezers Basic Chest; -86 deg. to -40 deg. C; 3 cu. ft.; Meet UL and CUL criteria; 208/24-V 60Hz	POR
1399022	Fisher Scientific* Isotemp* Freezers Basic Chest; -86 deg. to -40 deg. C; 3 cu. ft.; Meet UL and CUL criteria; 220V 50Hz	POR
1399025	Fisher Scientific* Isotemp* Freezers Basic Chest; -86 deg. to -40 deg. C; 7.0 cu. ft.; Meet UL and CUL criteria; 115V 60Hz	POR
1399002	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright 13 cu. ft.; 4 shelves; -86 to -50 deg. C; Solid-state controls, Alarm monitoring sys.; Air-cooled refrigeration; CFC-free; Meet UL/CUL criteria, 208/240V 60Hz	POR
1399003	Fisher Scientific* Isotemp* Freezers Basic -86 deg. C; Upright 13 cu. ft.; 4 shelves; -86 to -50 deg. C; Solid-state controls, Alarm monitoring sys.; Air-cooled refrigeration; CFC-free; Meet UL/CUL criteria, 220V 50Hz	POR
3986148ES	Fisher Scientific* Isotemp* Freezer, Enzyme 20.6 cu. ft.; 115V 60Hz	POR
3986154ES	Fisher Scientific* Isotemp* Freezer, Enzyme 5.0cu. ft.; 115V 60Hz	POR
13986525F	Fisher Scientific* Isotemp* Freezer, Explosion-Proof, 30 cu. ft., -30 deg. to -18 deg. C, 1 hinged solid door, 1/3hp, manual defrost, 120V 60Hz	POR
13986150	Fisher Scientific* Isotemp* Freezer, Explosion-Proof, 20.6 cu. ft., -20 deg. to -12 deg. C, 1 hinged solid door, 1/4hp, manual defrost, 115V 60Hz	POR
3986428FA	Fisher Scientific* Isotemp* Freezer, Flammable-materials Storage with Alarm 30 cu. ft., -25 to -10C, 1 hinged solid door, 1/3 hp, manual defrost, 115V 60Hz	POR
13986428F	Fisher Scientific* Isotemp* Freezer, Flammable-materials Storage 30 cu. ft., -25 to -10C, 1 hinged solid door, 1/3 hp, manual defrost, 115V 60Hz	POR
3986428FR	Fisher Scientific* Isotemp* Freezer, Flammable-materials Storage with Recorder 30 cu. ft., -25 to -10C, 1 hinged solid door, 1/3 hp, manual defrost, 115V 60Hz	POR
13986149	Fisher Scientific* Isotemp* Freezer, Flammable-materials Storage 20.6 cu. ft., -20 to -12C, 1 hinged solid door, 1/4hp, manual defrost, 115V 60Hz	POR
13986328F	Fisher Scientific* Isotemp* Freezer, General-purpose, 30 cu. ft., -25degree to -10degreeC, 1 hinged solid door, 1/3 hp, 115V 60Hz	POR

Prices mentioned are for one unit unless pack size is mentioned in the description

Contact: India Toll Free.: 1 800 209 7001 Fax: 022-6680 3001 / 02 e-mail: qfc.customer@thermofisher.com